ANDROID TOTAL STATION




STEL

AXIS 9B



AXIS 9 is equipped with a 5" high-resolution touchscreen and runs on the Android 9 operating system, which features the iconic and graphic program onboard. The measuring and staking out tasks. AXIS 9 is boosts your efficiency in any where.





Realtime Location Plan

Strong graphical capability allows viewing location plan after each measure.



Capable to import CAD file to stake out.



Measure the instrument height from advanced laser plummet.



Android 9

Easy and smooth UI Google Service Internet Connection

SPECIFICATIONS

SYSTEM

OS Android 9.0 Processor MT6735

Internal Memory RAM 3GB, ROM 32GB

TELESCOPIC

Length 154mm

Diameter Telescopic: 45mm; EMD: 50mm

Magnification 30x
Image Erect
Field of View 1°30'
Resolving Power 3"
Minimum Focus 1.5m

DISTANCE

Single Prism Range 5,000m

Accuracy AXIS 9: ±(2mm+2mm*D)m.s.e

AXIS 9P: ±(1mm+1mm*D)m.s.e

Non-prism Range AXIS 9: 1,500m

AXIS 9P: 1,000m

Accuracy $\pm (3mm+2mm*D)m.s.e$ Measuring Time Fine: 0.3s; Normal: 0.2s

Meteorologic Correction Auto Sensor
Prism Constant Manual

ANGLE

Accuracy AXIS 9: 2"

AXIS 9P: 1"

Method Absolute Encoding

Detecting System AXIS 9: H: dual; V: dual

AXIS 9P: H: quadruple; V: quadruple

Minimum Reading 1"/5"/10"

Diameter of Circle 79mm

Vertical Angle 0° Zenith: 0°; Horizontal: 0° Unit 360°/400gon/6400mil

DISPLAY

Display Unit 5" color touch LCD

No. of Displays 2

Buttons 2 volume buttons, 1 power button on

each display

GUIDE LIGHT

Type Red+yellow flashing LEDs

Wokring Range 150m

LASER PLUMMET - AutoHI

Type Class II red laser

Measuring Range 0.6-2.0m
Minimum Reading 1mm
Distance Accuracy 3mm

Deviation 0.4mm @ 1.5m height
Spot Diameter 1.5mm @ 1.5m height

TILT CORRECTION

Tilt Sensor Dual axis
Method Liquid electric

Range 4'
Resolution 1"

LEVEL

Plate Level 30"/2mm

Circular Level 8'/2mm

DATA INTERFACE

Data Interface USB2.0, MicroUSB, RS-232

Wireless Bluetooth 2.0/4.2, SIM card, Wi-Fi

GENERAL

Quick-meas Button Yes

Weight 6kg

Dimension 353 (H) * 206 (L): 200 (W) mm

Operating Temperature -20°C to 50°C

Battery Li-on battery, 7.4V, 5,000mAh

Water & Dust Proof IP55
Working Duration 10h





(O) **(**>

