

AUTO LEVEL ALS-32



MAGNIFICATION	32x
EFFECTIVE OBJECTIVE APERTURE	38mm
STANDARD DEVIATION IN 1KM	1.0mm
IMAGE	Erect
RETICLE	Cross reticle
FIELD OF VIEW	1°20'
MINIMUM FOCUS DISTANCE	0.3m
MULTIPLICATION CONSTANT	100
ADDITIVE CONSTANT	0
COMPENSATOR TYPE	Magnetic-damped
COMPENSATOR RANGE	±15'
COMPENSATOR ACCURACY	±0.5"
ACCURACY OF CIRCULAR BUBBLE	8'/2mm
CIRCULAR GRADUATION	360° or 400 gon
WORKING ENVIRONMENT	-30°C to +50°C
PROTECTION	IP54
SIZE	251*144*138mm
WEIGHT	1.8kg



AUTO LEVEL ALC-32

MAGNIFICATION	32x
EFFECTIVE OBJECTIVE APERTURE	40mm
STANDARD DEVIATION IN 1KM	1.0mm
IMAGE	Erect
RETICLE	Cross reticle
FIELD OF VIEW	1°20'
MINIMUM FOCUS DISTANCE	0.3m
MULTIPLICATION CONSTANT	100
ADDITIVE CONSTANT	0
COMPENSATOR TYPE	Air
COMPENSATOR RANGE	±15'
COMPENSATOR ACCURACY	±0.3"
ACCURACY OF CIRCULAR BUBBLE	8'/2mm
CIRCULAR GRADUATION	360° or 400 gon
WORKING ENVIRONMENT	-20°C to +50°C
PROTECTION	IP54
SIZE	251*144*138mm
WEIGHT	1.8kg