

Digital Level

STEC

DLS-15 / DLS-07



- High accuracy up to 0.7 / 1.5mm
- Trigger key
- Clear digital reading
- Magnetic-damped compensation

SPECIFICATIONS

DLS-15

DLS-07

HEIGHT ACCURACY Standard deviation for 1km of double leveling	1.5mm 2.0mm (optical measure)	0.7mm
DISTANCE Distance Accuracy Distance Range	D<10m: 10mm D>10m: D*0.001 2-110m	
MINIMUM DISPLAY Height Measurement Distance Measurement	0.1mm/1mm 0.01m/0.1m	
MEASURE PERFORMANCE Measuring Time	3s	
TELESCOPE Magnification Resolving Power Field of View Multiple Constant Additive Constant	32X 3" 1°30' 100 0	
COMPENSATOR Type Range Accuracy	Magnetic-damped 12' 0.5"/1' 0.3"/1'	
DATA STORAGE Internal Storage Point Name Connection External Storage	16MB (>100,000 points) Increasing/decreasing/customized Mini-USB Unavailable SD card	
LEVEL Circular Vial	8'/2mm	
DISPLAY & KEYBOARD Display Keyboard	128*32dpi LCD 16 keys + 1 power/trigger button	160*64dpi LCD
POWER SUPPLY Battery Operating Time	Rechargeable Li-on Battery, 2000mAh 20h	
GENERAL Working Temperature Dimension Weight Water & Dust Proof	-20°C - 50°C 230*150*210mm 2.5kg IP55	